

Container specifications

20' Standard – steel



Description	Non-metric	Metric
Maximum payload	62,170 lb	28,200 kg
Dimensions	20' x 8' x 8'6"	20' x 8' x 8'6"
Volume	1,165 cubic feet	33 m ³
Door openings, width	7' 8 1/16"	2,350 mm
Door openings, height	7' 5 1/2"	2,274 mm
Internal, length	19' 4 1/8"	5,896 mm
Internal, width	7' 8 1/2"	2,350 mm
Internal, height to load line	7' 10 3/16"	2,393 mm
Weight, gross	67,200 lb	30,480 kg
Weight, tare	5,030 lb	2,280 kg

40' Standard – steel



Description	Non-metric	Metric
Maximum payload	63,493 lb	28,800 kg
Dimensions	40' x 8' x 8'6"	40' x 8' x 8'6"
Volume	2,366 cubic feet	67 m ³
Door openings, width	7' 8 1/8"	2,340 mm
Door openings, height	7' 5 1/2"	2,274 mm
Internal, length	39' 5 11/16"	12,032 mm
Internal, width	7' 8 1/2"	2,350 mm
Internal, height to load line	7' 10 3/16"	2,393 mm
Weight, gross	71,650 lb	32,500 kg
Weight, tare	8,157 lb	3,700 kg

40' high – steel



Description	Non-metric	Metric
Maximum payload	58,380 lb	28,620 kg
Dimensions	40' x 8' x 9'6"	40' x 8' x 9'6"
Volume	2,684 cubic feet	76 m ³
Door openings, width	7' 8 1/8"	2,340 mm
Door openings, height	8' 5 7/16"	2,577 mm
Internal, length	39' 5 2/3	12,032 mm
Internal, width	7' 8 1/2"	2,352 mm
Internal, height to load line	7' 3 9/10"	2,679 mm
Weight, gross	67,200 lb	30,480 kg
Weight, tare	8,820 lb	4,000 kg

45' high – steel



Description	Non-metric	Metric
Maximum payload	60,848 lb	27,600 kg
Dimensions	45' x 8' x 9'6"	45' x 8' x 9'6"
Volume	3,036 cubic feet	85 m ³
Door openings, width	7' 8 1"	2,340 mm
Door openings, height	8' 5 12"	2,585 mm
Internal, length	44' 5 11"	13,556 mm
Internal, width	7' 8 9"	2,352 mm
Internal, height to load line	8' 10 3"	2,698 mm
Weight, gross	71,650 lb	32,500 kg
Weight, tare	10,803 lb	4,900 kg

45' high – aluminum



Description	Non-metric	Metric
Maximum payload	60,848 lb	27,600 kg
Dimensions	45' x 8' x 9'6"	45' x 8' x 9'6"
Volume	3,036 cubic feet	85 m ³
Door openings, width	7' 8 1"	2,340 mm
Door openings, height	8' 5 12"	2,585 mm
Internal, length	44' 5 11"	13,556 mm
Internal, width	7' 8 9"	2,352 mm
Internal, height to load line	8' 10 3"	2,698 mm
Weight, gross	71,650 lb	32,500 kg
Weight, tare	10,803 lb	4,900 kg