

SIZE	INTERIOR DIMENSIONS	DOOR OPENING	TOP OPENING	WEIGHT kg/lb			VOLUME
				max gross	tare	max payload	
20' DRY  20' x 8' x 8'6"	L: 5,896 mm 19'4 ^{1/8} " W: 2,350 mm 7'8 ^{1/2} " H: 2,393 mm 7'10 ^{3/16} "	W: 2,339 mm 7'8 ^{1/16} " H: 2,274 mm 7'5 ^{1/2} "		30,480 67,200	2,280 5,030	28,200 62,170	33.0 cbm 1,165 cu ft
40' HIGH CUBE DRY  40' x 8' x 9'6"	L: 12,032 mm 39'5 ^{11/16} " W: 2,350 mm 7'8 ^{1/2} " H: 2,697 mm 8'10 ^{1/8} "	W: 2,340 mm 7'8 ^{1/8} " H: 2,577 mm 8'5 ^{7/16} "		32,500 71,650	3,880 8,554	28,620 63,100	76.0 cbm 2,684 cu ft
40' DRY  40' x 8' x 8'6"	L: 12,032 mm 39'5 ^{11/16} " W: 2,350 mm 7'8 ^{1/2} " H: 2,393 mm 7'10 ^{3/16} "	W: 2,340 mm 7'8 ^{1/8} " H: 2,274 mm 7'5 ^{1/2} "		32,500 71,650	3,700 8,157	28,800 63,493	67 cbm 2,366 cu ft
20' REEFER  20' x 8' x 8'6" Temp +30°C to -30°C	L: 5,451 mm 17'10 ^{9/16} " W: 2,290 mm 7'6 ^{1/8} " H: 2,167 mm 7'1 ^{5/16} " *	W: 2,290 mm 7'6 ^{1/8} " H: 2,212 mm 7'3 ^{1/16} "		30,480 67,200	2,990 6,591	27,490 60,600	27 cbm 953 cu ft
40' HIGH CUBE REEFER  40' x 8' x 9'6" Temp +30°C to -30°C	L: 11,580 mm 37'11 ^{7/8} " W: 2,275 mm 7'5 ^{6/10} " H: 2,415 mm 7'11 ^{1/10} " *	W: 2,276 mm 7'5 ^{9/16} " H: 2,471 mm 8'1 ^{1/4} "		34,000 74,957	4,520 9,965	29,480 64,992	67.5 cbm 2,384 cu ft
40' HIGH CUBE STARFRESH  40' x 8' x 9'6" Controlled atmosphere	L: 11,578 mm 37'11 ^{13/16} " W: 2,280 mm 7'5 ^{3/4} " H: 2,425 mm 7'11 ^{1/2} " *	W: 2,278 mm 7'5 ^{11/16} " H: 2,473 mm 8'1 ^{5/16} "		34,000 74,957	4,600 10,140	29,400 64,992	64 cbm 2,261 cu ft
40' MAGNUM  40' x 8' x 9'6" Temp +30°C to -35°C	L: 11,578 mm 37'11 ^{13/16} " W: 2,280 mm 7'5 ^{3/4} " H: 2,450 mm 8'1 ² " *	W: 2,276 mm 7'5 ^{9/16} " H: 2,471 mm 8'1 ^{1/4} "		34,000 74,957	4,620 10,185	29,380 64,772	64 cbm 2,261 cu ft
20' OPEN TOP  20' x 8' x 8'6"	L: 5,919 mm 19'5" W: 2,346 mm 7'8 ^{5/16} " H: 2,286 mm 7'6"	W: 2,286 mm 7'6" H: 2,253 mm 7'4 ^{11/16} "	L: 5,490 mm 18'1 ^{1/16} " W: 2,223 mm 7'3 ^{1/2} "	30,480 67,196	2,280 5,027	28,000 61,728	
40' OPEN TOP  40' x 8' x 8'6"	L: 12,192 mm 40' W: 2,338 mm 7'8" H: 2,289 mm 7'6 ^{1/16} "	W: 2,289 mm 7'6 ^{1/16} " H: 2,253 mm 7'4 ^{11/16} "	L: 11,810 mm 38'8 ^{25/26} " W: 2,223 mm 7'3 ^{1/2} "	32,700 72,090	4,000 8,818	28,700 63,728	
40' HIGH OPEN TOP  40' x 8' x 9'6"	L: 12,192 mm 40' W: 2,348 mm 7'8 ^{3/8} " H: 2,653 mm 8'8 ^{4/9} "	W: 2,388 mm 7'8" H: 2,580 mm 8'5 ^{9/12} "	L: 11,810 mm 38'8 ^{25/26} " W: 2,223 mm 7'3 ^{1/2} "	30,480 67,196	4,000 8,818	26,480 58,377	
40' FIXED CORNER FLAT RACK  40' x 8' x 8'6"	L: 12,192 mm 40' W: 2,438 mm 8' H: 1,940 mm 6'4 ^{3/8} "	Length between:		40,000 88,183	5,500 12,125	34,500 76,058	2,114 6'11 ^{3/16} "
		Headers	Corner posts angle				
40' FLUSH FOLD FLAT RACK  40' x 8' x 8'6"	L: 12,192 mm 40' W: 2,438 mm 8' H: 1,940 mm 6'4 ^{3/8} "	12,080 mm 39'7 ^{9/16} "	11,796 mm 38'8 ^{3/8} "	40,000 88,183	5,500 12,125	34,500 76,058	2,224 7'3 ^{1/2} "
		12,058 mm 39'6 ^{11/16} "	11,662 mm 38'3 ^{1/8} "				
40' HIGH FLAT RACK  40' x 8' x 9'6"	L: 12,192 mm 40' W: 2,438 mm 8' H: 2,260 mm 7'4 ^{29/30} "	12,058 mm 39'6 ^{11/16} "	11,662 mm 38'3 ^{1/8} "	52,500 111,741	5,300 11,684	47,200 104,056	2,224 7'3 ^{1/2} "

Please note dimensions vary with container series - for dimensions of a specific unit please contact your local Safmarine office. Please check container doors for the payload and take note of individual countries road weight limitations. Equipment subject to availability.